



Tip Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN10 - PN250 veya ANSI 150 - 600 DN15 - DN300, 1/2" - 12" Gövde : GG-25, GGG40.3, GS-C25, 1.4408 Disk : 316 veya 304 Sit : 316 veya 304	Type Application : Steam, hot water, compressed air and other neutral media PN10 to PN250 or ANSI 150 to 600 DN15 to DN300, 1/2" to 12" Body : GG-25, GGG40.3, GS-C25, 1.4408 Disc : 316 or 304 Seats : 316 or 304	
Tip Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN10 - PN25 DN10 - DN50, 3/8" - 2" Gövde : GG-25, G-CuSn10 Disk : X20Cr13 Sit : X20Cr13	Type Application : Steam, hot water, compressed air and other neutral media PN10 to PN25 DN15 to DN50, 3/8" to 2" Body : GG-25, G-CuSn10 Disc : X20Cr13 Seats : X20Cr13	
Tip Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN10 - PN250 DN65 - DN150, 2,5" - 6" (isteğe bağlı otomatik basınç ayarlı) Gövde : GG-25, GGG40.3, GS-C25, 1.4408 Disk : 316 veya 304 Sit : 316 veya 304	Type Application : Steam, hot water, compressed air and other neutral media PN10 to PN250 DN65 to DN150, 2,5" to 6" (automatic pressure relief on request) Body : GG-25, GGG40.3, GS-C25, 1.4408 Disc : 316 or 304 Seats : 316 or 304	
Tip Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN10 - PN64 DN15 - DN300, 1/2" - 12" Gövde : GG-25, GGG40.3, GS-C25, 1.4408 Disk : 316 veya 304 Sit : Metal veya NBR	Type Application : Steam, hot water, compressed air and other neutral media PN10 to PN64 DN15 to DN300, 1/2" to 12" Body : GG-25, GGG40.3, GS-C25, 1.4408 Disc : 316 or 304 Seats : 316 or 304	

Tip Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN10 - PN100 veya ANSI 150 - 600 DN50 - DN600, 1/2" - 24" Gövde : GS-C25, 17CrMo55, 21Mn5 Disk : 316 veya 304 Mil : 13Cr, Stellite 6, 316	Type Swing Check Valve Application : Steam, hot water, compressed air and other neutral media PN10 up to PN100 or ANSI 150 up to 600 DN50 up to DN600, 2" up to 24" Body : GS-C25, 17CrMo55, 21Mn5 Disc : 304, 316 Trim : 13Cr, Stellite 6, 316	
Tip Çalpara çekvalf (Y-tip) Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN16 DN40 - DN150, 11/2" - 6" Gövde : GG-25 Disk : GX20Cr14 Mil : X20Cr13 Sızdırmazlık : CrNiSt-Grafit	Type Swing Check Valve (Y-Type) Application : Steam, hot water, compressed air and other neutral media PN16 DN40 to DN150, 11/2" to 6" Body : GG-25 Disc : GX20Cr14 Trim : X20Cr13 Seal : CrNiSt-Graphit	
Tip Çalpara çekvalf kilitlemeli Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN10 veya ANSI 150 DN40 - DN250, 11/2" - 10" Gövde : GG-25 Disk : GGG.50 Mil : X20Cr13 Sızdırmazlık : Klinger SIL 4400	Type Swing Check Valve with locking screw Application : Steam, hot water, compressed air and other neutral media PN10 or ANSI 150 DN40 to DN250, 1 1/2" to 10" Body : GG-25 Disc : GGG.50 Trim : X20Cr13 Seal : Klinger SIL 4400	
Tip Küre tipi çekvalf Uygulama : Buhar,sıcak su,basınçlı hava ve vb.akışkanlar PN10, PN16 veya ASA125 diğerleri isteğe bağlı DN40 - DN350, 1 1/2" - 24" Gövde : GG-25, GGG40, 1.4408 Küre : Alum 231 A,, Sızdırmazlık : Metal,PTFE veya NBR	Type Ball Check Valve Application : Steam, hot water, compressed air and other neutral media PN10, PN16 or ASA125 (other on request) DN40 to DN350, 1 1/2" to 24" Body : GG-25, GGG40, 1.4408 Ball : Alum 231 A, lined Seals : Metal, PTFE or NBR	

ÇEKVALFLER – CHECK VALVES

CANTEK

Tip	Yaylı tip	Type	Lift Check Valve	
Uygulama	: Buhar,sıcak su,basınçlı hava ve diğer doğal akışkanlar	Application	: Steam, hot water, compressed air and other neutral media	
PN16 -PN40 veya ANSI 150 DN15 - DN50, 1/2" - 2"		PN16 up to PN40 or ANSI 150 DN15 up to DN50, 1/2" up to 2"		
Gövde	: Ms58, 1.4408	Body	: Ms58, 1.4408	
disk	: Ms58, 1.4408	Disc	: Ms58, 1.4408	
conta	: NBR, PTFE	Seal	: NBR, PTFE	
Tip	Rückschlagklappe (Y-tip)	Type	Swing Check Valve (Y-Type)	
Uygulama	: Buhar,sıcak su,basınçlı hava ve diğer doğal akışkanlar	Application	: Steam, hot water, compressed air and other neutral media	
PN25 DN15 - DN50, 1/2" - 2"		PN25 DN15 to DN50, 1/2" to 2"		
Gövde	: Ms58, 1.4408	Body	: Ms58, 1.4408	
disk	: Ms58, 1.4408	Disc	: Ms58, 1.4408	
conta	: Metall/Metall	Seal	: Metal/Metal	
Tip	Üniversal-pirinç Yaylı boru tipi	Type	Universal - Brass Check Valve	
Uygulama	: Buhar,sıcak su,basınçlı hava ve diğer doğal akışkanlar	Application	: Steam, hot water, compressed air and other neutral media	
PN10 - PN25 DN10 - DN100, 3/8" - 4"		PN10 up to PN25 DN10 to DN100, 3/8" to 4"		
Gövde	: Ms58	Body	: Ms58	
Disk	: Ms58	Disc	: Ms58	
Conta	: NBR,PTFE	Spring	: Stainless Steel	
Yay	Paslanmaz çelik	Seal	: NBR	
Tip	Universal-paslanmaz Yaylı boru tipi	Type	Universal - Stainless Steel Check Valve	
Uygulama	: Buhar,sıcak su,basınçlı hava ve diğer doğal akışkanlar	Application	: Steam, hot water, compressed air and other neutral media	
PN16 DN8 - DN80, 1/4" - 4"		PN16 DN8 to DN80, 1/4" to 4"		
Gövde	: 304 veya 316	Body	: 1.4301	
Disk	: 304 veya 316	Disc	: 1.4301	
Conta	: FKM,PTFE	Spring	: 1.4301	
Yay	: 304 veya 316	Seal	: FKM,PTFE	