

|                                                                                                                                                      |                                                                                                                                                       |                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Tip</b><br><b>MONOBLOK</b><br><b>Redüksiyon geçişli</b><br><b>Hassas döküm</b>                                                                    | <b>Type</b><br><b>Ball Valve (1-piece body)</b><br><b>Reduced bore</b><br><b>Investment casting</b>                                                   |    |
| <b>Uygulama</b> : Kimyasal sıvılar<br>Endüstriyel akışkanlar                                                                                         | <b>Application</b> : Chemical plants<br>Industrial plants                                                                                             |                                                                                       |
| PN63 veya 1000 psi<br>DN8 -- DN50, 1/4" -- 2" NPT, BSP<br>Gövde : 316<br>Küre : 316 veya 304<br>Mil : 316 veya 304<br>Conta : R-PTFE takviyeli (15%) | PN63 or 1000 psi<br>DN8 up to DN50, 1/4" up to 2" NPT, BSP<br>Body : 316<br>Ball : 316 or 304<br>Stem : 316 or 304<br>Seats : R-PTFE reinforced (15%) |                                                                                       |
| <b>Tip</b><br><b>MONOBLOK</b><br><b>Redüksiyon geçişli</b><br><b>Dolu malzemeden işleme</b>                                                          | <b>Type</b><br><b>Ball Valve (1-piece body)</b><br><b>Reduced bore</b><br><b>Hexagon Bar-Material</b>                                                 |   |
| <b>Uygulama</b> : Kimya sanayi<br>Endüstriyel akışkanlar                                                                                             | <b>Application</b> : Chemical plants<br>Industrial plants                                                                                             |                                                                                       |
| PN63 veya 1000 psi<br>DN8 - DN50, 1/4" - 2" NPT, BSP<br>Gövde : 316<br>Küre : 316 veya 304<br>Mil : 316 veya 304<br>Conta : R-PTFE takviyeli (15%)   | PN63 or 1000 psi<br>DN8 up to DN50, 1/4" up to 2" NPT, BSP<br>Body : 316<br>Ball : 316 or 304<br>Stem : 316 or 304<br>Seats : R-PTFE reinforced (15%) |                                                                                       |
| <b>Tip</b><br><b>2-parçalı gövde</b><br><b>Aktuatör tablalı</b>                                                                                      | <b>Type</b><br><b>Ball Valve (2-piece body)</b><br><b>with ISO - top flange</b>                                                                       |  |
| <b>Uygulama</b> : Kimya ve genel amaçlı                                                                                                              | <b>Application</b> : Chemical plants<br>Industrial plants                                                                                             |                                                                                       |
| PN100 - PN130 veya 1500 - 2000 psi<br>DN8 - DN50, 1/4" 2" NPT, BSP<br>Gövde : 316<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)                 | PN100-130 or 1500-2000 psi<br>DN8 up to DN50, 1/4" up to 2" NPT, BSP<br>Body : 316<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)                |                                                                                       |
| <b>Tip</b><br><b>2-parçalı gövde</b>                                                                                                                 | <b>Type</b><br><b>Ball Valve (2-piece body)</b>                                                                                                       |  |
| <b>Uygulama</b> : Kimya ve genel endüstri                                                                                                            | <b>Application</b> : Chemical plants<br>Industrial plants                                                                                             |                                                                                       |
| PN63 veya 1000 psi<br>DN8 - DN80, 1/4" - 3" NPT, BSP<br>Gövde : 316<br>Küre : 316<br>Mil : 316<br>Conta : PTFE                                       | PN63 or 1000 psi<br>DN8 up to DN80, 1/4" up to 3" NPT, BSP<br>Body : 316<br>Ball : 316<br>Stem : 316<br>Seats : PTFE virgin                           |                                                                                       |

|                                                                      |                                                                      |                                                                                       |
|----------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Tip</b> 2-parçalı gövde<br>DIN3202-M3                             | <b>Type</b> Ball Valve (2-piece body)<br>f.t.f. acc. DIN3202-M3      |    |
| <b>Uygulama</b> : Kimya ve endüstriyel uygulamalar                   | <b>Application</b> : Chemical plants<br>Industrial plants            |                                                                                       |
| PN100 - PN130 veya 1500 - 2000 psi<br>DN8 - DN50, 1/4" - 2" NPT, BSP | PN100-130 or 1500-2000 psi<br>DN8 up to DN50, 1/4" up to 2" NPT, BSP |                                                                                       |
| Gövde : 316<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)       | Body : 316<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)       |                                                                                       |
| <b>Tip</b> 2-parçalı gövde<br>Aktuatör tablalı                       | <b>Type</b> Ball Valve (2-piece body)<br>with ISO - top flange       |   |
| <b>Uygulama</b> : Kimya ve endüstride                                | <b>Application</b> : Chemical plants<br>Industrial plants            |                                                                                       |
| PN63 veya 800 - 1000 psi<br>DN8 - DN80, 1/4" - 3" NPT, BSP           | PN63 or 800 -1000 psi<br>DN8 up to DN50, 1/4" up to 3" NPT, BSP      |                                                                                       |
| Gövde : 316<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)       | Body : 316<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)       |                                                                                       |
| <b>Tip</b> 2-parçalı gövde<br>diştan dişli                           | <b>Type</b> Ball Valve (2-piece body)<br>Male Thread (Ermeto)        |  |
| <b>Uygulama</b> : Kimya ve endüstride                                | <b>Application</b> : Chemical plants<br>Industrial plants            |                                                                                       |
| PN63 veya 1000 psi<br>DN8 - DN50, 1/4" - 2" NPT, BSP                 | PN63 or 1000 psi<br>DN8 up to DN50, 1/4" up to 2" NPT, BSP           |                                                                                       |
| Gövde : 316<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)       | Body : 316<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)       |                                                                                       |
| <b>Tip</b> 3-parçalı gövde<br>Aktuatör tablalı                       | <b>Type</b> Ball Valve (3-piece body)<br>Mount Direct Top Flange     |  |
| <b>Uygulama</b> : Kimya ve endüstride                                | <b>Application</b> : Chemical plants<br>Industrial plants            |                                                                                       |
| PN63 veya 1000 psi<br>DN8 - DN100, 1/4" - 4" BSP, NPT,SW, BW         | PN63 or 1000 psi<br>DN8 - DN100, 1/4" - 4" BSP, NPT,SW, BW           |                                                                                       |
| Gövde : 316<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)       | Body : 316<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)       |                                                                                       |

|                                                                           |                                       |                                                                           |                                                |
|---------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------|------------------------------------------------|
| <b>Tip</b>                                                                | <b>3-parçalı gövde diřli bağlantı</b> | <b>Type</b>                                                               | <b>Ball Valve (3-piece body) Threaded ends</b> |
| <b>Uygulama</b>                                                           | : Kimya ve endüstride                 | <b>Application</b>                                                        | : Chemical plants<br>Industrial plants         |
| PN63 veya 1000 psi<br>DN8 - DN100, 1/4" - 4" NPT, BSP                     |                                       | PN63 or 1000 psi<br>DN8 up to DN100, 1/4" up to 4" NPT, BSP               |                                                |
| Gövde : 1.4408, 1.0619<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%) |                                       | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%) |                                                |



|                                                                           |                                      |                                                                           |                                                      |
|---------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------|------------------------------------------------------|
| <b>Tip</b>                                                                | <b>3-parçalı gövde kaynak ağızlı</b> | <b>Type</b>                                                               | <b>Ball Valve (3-piece body) with Butt Weld ends</b> |
| <b>Uygulama</b>                                                           | : Kimya ve endüstride                | <b>Application</b>                                                        | : Chemical plants<br>Industrial plants               |
| PN63 veya 1000 psi<br>DN8 - DN100, 1/4" - 4" BW                           |                                      | PN63 or 1000 psi<br>DN8 up to DN100, 1/4" up to 4" BW                     |                                                      |
| Gövde : 1.4408, 1.0619<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%) |                                      | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%) |                                                      |



|                                                                           |                                         |                                                                           |                                                        |
|---------------------------------------------------------------------------|-----------------------------------------|---------------------------------------------------------------------------|--------------------------------------------------------|
| <b>Tip</b>                                                                | <b>3-parçalı gövde soket bağlantılı</b> | <b>Type</b>                                                               | <b>Ball Valve (3-piece body) with Sucked Weld ends</b> |
| <b>Uygulama</b>                                                           | : Kimya ve endüstride                   | <b>Application</b>                                                        | : Chemical plants<br>Industrial plants                 |
| PN63 veya 1000 psi<br>DN8 - DN100, 1/4" - 4" SW                           |                                         | PN63 or 1000 psi<br>DN8 up to DN100, 1/4" up to 4" SW                     |                                                        |
| Gövde : 1.4408, 1.0619<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%) |                                         | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%) |                                                        |



|                                                                              |                              |                                                                           |                                         |
|------------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------|-----------------------------------------|
| <b>Tip</b>                                                                   | <b>3-parçalı gövde W-tip</b> | <b>Type</b>                                                               | <b>Ball Valve (3-piece body) W-Type</b> |
| <b>Uygulama</b>                                                              | : Kimya ve endüstride        | <b>Application</b>                                                        | : Chemical plants<br>Industrial plants  |
| PN100 - PN130 veya 1500 - 2000 psi<br>DN8 - DN50, 1/4" - 2" NPT, BSP, BW, SW |                              | PN100 - 130 or 1500 - 2000 psi<br>DN8 - DN50, 1/4" - 2" NPT, BSP, BW, SW  |                                         |
| Gövde : 1.4408, 1.0619<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)    |                              | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%) |                                         |



|                                                                                                                                                    |                                                                                                                                                                                             |                                                                                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Tip</b> : 3-parçalı gövde<br><b>Uygulama</b> : Kaynak ağızlı<br>: Kimya ve endüstride<br><br>PN63 veya 1000 psi<br>DN8 - DN100, 1/4" - 4"       | <b>Type</b> : Ball Valve (3-piece body)<br><b>Application</b> : with extended BW-Ends<br>: Chemical plants<br>: Industrial plants<br><br>PN63 or 1000 psi<br>DN8 up to DN100, 1/4" up to 4" |    |
| Gövde : 1.4408, 1.0619<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)                                                                          | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)                                                                                                                   |                                                                                       |
| <b>Tip</b> : 3-parçalı gövde<br><b>Uygulama</b> : klamp bağlantı<br>: Kimya ve endüstride<br><br>PN63 veya 800 -1000 psi<br>DN8 - DN100, 1/4" - 4" | <b>Type</b> : Ball Valve (3-piece body)<br><b>Application</b> : with Clamb-Ends<br>: Chemical plants<br>: Industrial plants<br><br>PN63 or 800 - 1000 psi<br>DN8 up to DN100, 1/4" up to 4" |   |
| Gövde : 1.4408<br>Küre : 316<br>Mil : 316<br>Conta : PTFE                                                                                          | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : PTFE                                                                                                                           |                                                                                       |
| <b>Tip</b> : 3-parçalı gövde<br><b>Uygulama</b> : kamlock bağlantı<br>: Kimya ve endüstride<br><br>PN63 veya 1000 psi<br>DN8 - DN100, 1/4" - 4"    | <b>Type</b> : Ball Valve (3-piece body)<br><b>Application</b> : with CAMLOCK-Ends<br>: Chemical plants<br>: Industrial plants<br><br>PN63 or 1000 psi<br>DN8 up to DN100, 1/4" up to 4"     |  |
| Gövde : 1.4408, 1.0619<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)                                                                          | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)                                                                                                                   |                                                                                       |
| <b>Tip</b> : 3-parçalı gövde<br><b>Uygulama</b> : victolic bağlantı<br>: Kimya ve endüstride<br><br>PN63 veya 1000 psi<br>DN8 - DN100, 1/4" - 4"   | <b>Type</b> : Ball Valve (3-piece body)<br><b>Application</b> : with VICTAULIC-Ends<br>: Chemical plants<br>: Industrial plants<br><br>PN63 or 1000 psi<br>DN8 up to DN100, 1/4" up to 4"   |  |
| Gövde : 1.4408, 1.0619<br>Küre : 316<br>Mil : 316<br>Conta : R-PTFE (15%)                                                                          | Body : 1.4408, 1.0619<br>Ball : 316<br>Stem : 316<br>Seats : R-PTFE (15%)                                                                                                                   |                                                                                       |